



INDUSTRY

DDK-LED HBR HE RACKS (Asymmetric) PRODUCT RANGE

BASIC PARAMETERS

Light Source	LED
IP Rating	IP 65
CRI (Ra>)	75
Warranty (Year)	5
Service Lifetime	> 80 000 hours
Material	Aluminium
Optics	LED modules
LIDC	Symmetric (20x60°)
Operating Temp.	-30/+60 °C
Input Voltage	110-277 V / 50HZ-60HZ
Driver brand	MEANWELL
Certification	CE, GS, RoHS, UL
Photometric test	acc.STN EN 13032
Photometric Lab.	Skúšobňa FEI STU, Ilkovičova 3, BA



DDK-LED HBR HE RACKS represents sophisticated highpower LED luminaires dedicated for long narrow spaces such as aisles in warehouses and other industrial areas. An asymmetric curve is characteristic for DDK-LED HBR HE RACKS. High value of CRI > 75 Ra brings optical performance which is essential for the correct performance of a working area where daylight is limited. CRI > 95 Ra is possible on order. The proved IP 65 degree for industrial environments prolongs the life of luminaires by protecting them from dust and moisture.

Features:

- MEANWELL driver
- Energy class A+
- Top quality materials used
- Suspended / Surfaced mounting
- ies/td files are available on request
- Supplied complete with accessories
- Highly-resistant IP 68 connector used

Applications:

long narrow spaces such as aisles in warehouses and other industrial areas



Type	Power +/-2%	Lumen +/- 9.3%	Color rendering index	Color temperature +/- 100K
	(W)	(lm)	CRI (Ra>)	CCT (K)
DDK-HBR HE 40	40	> 4800	75	3000 -6500K
DDK-HBR HE 80	80	>9600	75	3000 -6500K
DDK-HBR HE 110	110	>13200	75	3000 -6500K
DDK-HBR HE 150	150	>18000	75	3000 -6500K



www.ddk-led.eu

ddkLED
TECHNOLOGY SERVICES

business@ddk-led.eu

