



OFFICE & PUBLIC SPACE

DDK - LED DL (DOWNLIGHT) PRODUCT RANGE

BASIC PARAMETERS

Light Source	LED
IP Rating	IP 44
UGR	<19
CRI (Ra>)	70
Warranty (Year)	2
LED Operating Life	> 80 000 hrs
Material	Aluminum Alloy+PMMA
Fixture color	Silver
Operating Temp.	-20 / +40
Input Voltage	90-264VAC / 127-370 VDC
Certification	CE, PSE, RoHS, SAA, UL
Photometric test	acc.STN EN 13032
Photometric Lab.	Skúšobňa FEI STU, Ilkovičova 3, BA



DDK-LED DL (Downlight) - represents super flat LED luminaires designed for installation directly into the drywall. Excellent thermal management and refined aluminum extend the lifespan of the LEDs up to 80 000 hours. Using LEDs offers the best quality and great lumen output. Easy to install. The use in boutiques, receptions, shops, showrooms, entrance halls and corridors is highly recommended due to outstanding technical parameters.

Features:


Energy class A+
easy installation
ies/.ldt files on request
external high PF constant current LED driver
instant on/off, No UV/ flickering, no humming
edgelite, bright luminosity, soft and comfortable for eyes
better heat sink, with temperature rise less than 20 deg., good for extending lifespan
aluminium plate for dissipation with coefficient of thermal conductivity more than 1.2.

Applications:

offices, boutiques, receptions, shops, showrooms, entrance halls, corridors



Type	Power +/-10% (W)	Lumen +/- 9,3% (lm)	Color Rendering Index CRI (Ra)	Color temperature +/-100K CCT (K)	Diameter Ø mm x H
DDK-LED DL25	25	2200	> 70	WW (2800K-3200K) NW (4000K-4500K) PW (5000K-5500K) W (6000K - 6500K)	Ø250xH48



www.ddk-led.eu

ddk•LED
TECHNOLOGY SERVICES

business@ddk-led.eu

