



OFFICE & PUBLIC SPACE

DDK - LED RP (ROUND PANEL)

PRODUCT RANGE

BASIC PARAMETERS

Light Source	LED
IP Rating	IP 44
UGR	<19
CRI (Ra>)	70
Warranty (Year)	2
LED Operating Life	> 80 000 hrs
Material	Aluminum Alloy+PMMA
Fixture color	Silver
Operating Temp.	-20 / +40
Input Voltage	90-264VAC 50-60Hz
Certification	CE, PSE, RoHS, SAA, UL
Photometric test	acc.STN EN 13032
Photometric Lab.	Skúšobňa FEI STU, Ilkovičova 3, BA



DDK-LED RP (Round Panel) - represents super flat LED luminaires designed for installation directly into the drywall. Excellent thermal management and refined aluminum extend the lifespan of the LEDs up to 80 000 hours. Using LEDs offers the best quality and great lumen output. Easy to install. The use in boutiques, receptions, shops, showrooms, entrance halls and corridors is highly recommended due to outstanding technical parameters.

Features:


- Energy class A+
- LED files on request
- ultra slim panel with thickness only 13mm
- external high PF constant current LED driver
- Instant on/off, No UV flickering, no humming
- customized size, power consumption and frame color
- edgelite, bright luminosity, soft and comfortable for eyes
- 50% less power consumption than traditional light sources

Applications:

offices, boutiques, receptions, shops, showrooms, entrance halls, corridors



Type	Power +/-10% (W)	Lumen +/- 9,3% (lm)	Color Rendering Index CRI (Ra)	Color temperature +/-100K CCT (K)	Diameter Ø mm x H
DDK-LED RP	18	1170	> 70	WW (2800K-3200K) NW (4000K-4500K) PW (5000K-5500K) W (6000K - 6500K)	Ø240xH13



www.ddk-led.eu

ddkLED
TECHNOLOGY SERVICES

business@ddk-led.eu

