



INDUSTRY

DDK-PRIMUS LED T8 21200

BASIC PARAMETERS

Power	2x18W
Lamp holder	G13
P Rating	IP66
Luminous flux	3879lm
CRI (Ra>)	>80
CCT	4000K
Material and components	quality PC in grey color, connecting clips, steel reflector, modified white plate powder coating, diffuser-clear PC
Dimensions mm	L:1272mm, W:145mm, H:111mm
Lifetime	> 80 000 hrs
Warranty (years)	3 years
Input voltage	AC100-230V 50-60Hz
Certification	CE, PSE, RoHS, SAA, UL
Photometric test	acc.STN EN 13032
Photometric Lab	Skúšobňa FEI STU, Ilkovičova 3, BA



Features:
No glare
Indoor Use
Energy class A+
Short circuit protection
Constant current accuracy 3%
Long lifespan, High light efficiency
Energy saving, no mercury, no UV or IR radiation
Special optical design, lighting distribution uniformity

Applications:

Replacement for conventional T8 fluorescent tubes
Hotels
Conference/meeting room
Commercial Areas
Residential/Institution Buildings
Schools
Hospitals



www.ddk-led.eu

ddk•LED
TECHNOLOGY SERVICES

business@ddk-led.eu

